AMENDMENT OF SOLICITATION/MODIFICATION OF CONTRACT			1. CONTRACT ID C	ODE	PAGE 1	DF PAGES
2. AMENDMENT/MODIFICATION NO.	3. EFFECTIVE DATE	4. REQUISITION/PURCHA	SE REQ. NO.	5. PROJEC	T NO. (If app	licble)
6. ISSUED BY CODE	11/18/13	N/A 7. ADMINISTERED BY (If	other than Item 6)	CODE		
NASA Shared Services Center (N Building 1111, C Road Stennis Space Center, MS 39529					L	
8. NAME AND ADDRESS OF CONTRACTOR (No., street, co.	unty, State and ZIP Code)		(X) 9A. AMENDME	NT OF SOLICIA	ATION NO.	_
		NNX14SBIRSTTR-GENERAL 9B. DATED (SEE ITEM 11) 11/14/13 10A. MODIFICATION OF CONTRACT/ORDER NO. 10B. DATED (SEE ITEM 11)				
	CILITY CODE		OLIGITATIONS			
II. IHIS IIE	VI UNLT APPLIES TO	AMENDMENTS OF S	—		_	
12. ACCOUNTING AND APPROPIRATION DATA (If required 13. THIS ITEM O IT MODIFIES CHECK ONE A. THIS CHANGE ORDER IS ISSUED PURS NO, IN ITEM 10A.	NLY APPLIES TO MO	ODIFICATION OF CON DER NO. AS DESCRIE BY) THE CHANGES SET FORTI	BED IN ITEM 14.	1	ONTRACT OF	RDER
B. THE ABOVE NUMBERED CONTRACT/C appropriation date, etc.) SET FORTH IN				changes in payi	ing office,	
C. THIS SUPPLEMENTAL AGREEMENT IS	ENTERED INTO PURSUANT	TO AUTHORITY OF:				
D. OTHER (Specify type of modification an	d authority)			·		
E. IMPORTANT: Contractor is not,	is required to sign th	nis document and retu	rn — 0	opies to th	ne issuing	office.
14. DESCRIPTION OF AMENDMENT/MODIFICATION (Organ	nized by UCF section heading	gs, including solicitation/contr	act subject matter wh	ere feasible.)		
The purpose of this amendment	is to:					
 revise wording in las replace Subtopic S1.0 	t paragraph of 2 Microwave Tec	ARMD description of the ARMD d	n in Sectio Lemote Sensi	n 9.1; a ng in it	and s enti	rety.
See Summary of Changes on SF30	continuation p	page.				
Except as provided herein, all terms and conditions of the do	ocument referenced in Item 9	A or 10A, as heretofore char	nged, remains unchan	ged and in full	force and eff	ect.
15A. NAME AND TITLE OF SIGNER (Type or print)		16A. NAME AND TITLE OF Cassandra W	CONTRACTING OFFI	CER (Type or p		-
15B. CONTRACTOR/OFFEROR	15C. DATE SIGNED	Lead Contra	MEBICA /	ms)	16C. D	ATE SIGNE
(Signature of person authorized to sign)	— <u> </u>		of Contracting Office	y -	— {\	10/20

SECTION SF 30 BLOCK 14 CONTINUATION PAGE

SUMMARY OF CHANGES

1) **FROM**:

In 2012, ARMD started issuing more focused solicitations by rotating subtopics every other year. The reduction in the scope of the solicitation does not imply a change in interest in a given area. For example, in 2012 we solicited proposals for airframe noise reduction and efficiency improvement (through drag reduction). In 2014 we are soliciting proposals for **engine noise and efficiency reductions**. Then in 2015 we plan to return to airframe noise and efficiency improvement.

TO:

In 2012, ARMD started issuing more focused solicitations by rotating subtopics every other year. The reduction in the scope of the solicitation does not imply a change in interest in a given area. For example, in 2012 we solicited proposals for airframe noise reduction and efficiency improvement (through drag reduction). In 2014 we are soliciting proposals for **engine efficiencies and noise reduction**. Then in 2015 we plan to return to airframe noise and efficiency improvement.

2) S1.02 Microwave Technologies for Remote Sensing

Lead Center: GSFC

Participating Center(s): JPL, LaRC

NASA employs active (radar) and passive (radiometer) microwave sensors for a wide range of remote sensing applications (for example, see: http://www.nap.edu/catalog/11820.html). These sensors include low frequency (less than 10 MHz) sounders to G-band (160 GHz) radars for measuring precipitation and clouds, for planetary landing, upper atmospheric monitoring, and global snow coverage (SCLP). We are seeking proposals for the development of innovative technologies to support these future radar and radiometer missions and applications. The areas of interest for this call are listed below:

- W-band Solid State Power Amplifier: Freq: 94 GHz +/- 500 MHz, Peak power: > 50 W, Duty cycle: > 20 %, Gain: > 40 dB, Gain flatness within band: <+/- 1 dB, Phase linearity within band: < +/- 1 degree, On/off switching speed: < 1 μs, Noise figure: < 15 dB, Spurious: < -60 dBc, Harmonic: < -25 dBc
- 640 GHz Polarimeter I, Q, U Channels, Polarimetric measurements to provide microphysical parameterization of ice clouds applicable to ACE

- Broadband low noise cryogenic amplifier operating between 1 and 6 GHz
- G-band (140-220 GHz) Components: 3-port strip line/CPW based switch (20 dB isolation, 1 dB loss, 1 kHz switching frequency), G-band (140-220 GHz) Components: Isolator with isolation > 15 dB, Insertion loss < 1.2 dB
- High power Solid-State Ka-band Transmitter: Psat > 200W, Duty Cycle > 20%, DC to RF Efficiency > 30%, Gain > 50 dB
- Very high-efficiency VHF Power Amplifier for CubeSats: Center frequency range:
 40MHz to 100MHz, Fractional bandwidth: 20%, Psat >25W, Gain > 40 dB, Efficiency > 90%
- Technology for low-power, rad-tolerant broad band spectrometer back ends for microwave radiometers. Includes: digitizers with 20 Gsps, 20 GHz bandwidth, 4 or more EOB and a simple interface to FPGA; ASIC implementations of polyphase spectrometer digital signal processing with ~1 watt/GHz;
- Back ends for microwave radiometers and sounders including compact low power RFI
 mitigation hardware for upgrading existing systems and low-power, low-mass filter back
 ends with >5 GHz spectral coverage, 200 MHz resolution, and less than one watt.

End Summary of Changes